
PILING & VIBRO EQUIPMENT

Specification sheet
PVE 1000 STAGE V / TIER 4F
Hydraulic Power Pack

English




Specifications :	PVE 1000 STAGE V / TIER 4F	
Diesel Engine	Volvo TAD 1384 VE (2x)	
Max. theoretical power	750/1020	kW/HP
Max. frequency	1900	rpm
Max. operating pressure	350	bar
Hydraulic pump	Parker	
Max. oil flow	1051	L/min
Diesel oil	1820	L
DEF (AdBlue) capacity	90	L
Hydraulic oil	2130	L
Weight without fuel	12430	kg
Weight filled up	14000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT

Technische Daten
PVE 1000 STAGE V / TIER 4F
Aggregat

Deutsch




Technische Daten :	PVE 1000 STAGE V / TIER 4F	
Dieselmotor	Volvo TAD 1384 VE (2x)	
Max. theoretische Leistung	750/1020	kW/HP
Max. Drehzahl	1900	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Parker	
Max. Fördermenge	1051	L/min
Diesel Öl	1820	L
DAF (AdBlue) kapazität	90	L
Hydraulische Öl	2130	L
Gewicht ohne Diesel Öl	12430	kg
Gewicht	14000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT

Spécifications
PVE 1000 STAGE V / TIER 4F
Groupe hydraulique

Français




Spécifications	PVE 1000 STAGE V / TIER 4F	
Moteur Diesel	Volvo TAD 1384 VE (2x)	
Puissanse théorique max.	750/1020	kW/HP
Max. fréquence	1900	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Parker	
Débit d'huile max.	1051	L/min
Huile diesel	1820	L
Capacité FED (AdBlue)	90	L
Huile hydraulique	2130	L
Poids sans huile diesel	12430	kg
Poids	14000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT

Specificaties
PVE 1000 STAGE V / TIER 4F
Hydraulisch aggregaat

Nederlands




Specificaties	PVE 1000 STAGE V / TIER 4F	
Dieselmotor	Volvo TAD 1384 VE (2x)	
Max. theoretisch vermogen	750/1020	kW/HP
Max. toerental	1900	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Parker	
Max. olie doorstroming	1051	L/min
Diesel olie	1820	L
DEF (AdBlue) capaciteit	90	L
Hydraulische olie	2130	L
Gewicht zonder diesel	12430	kg
Gewicht	14000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT

Especificaciones
PVE 1000 STAGE V / TIER 4F
Unidat de potencia

Español



Especificaciones	PVE 1000 STAGE V / TIER 4F	
Motor de diesel	Volvo TAD 1384 VE (2x)	
Potencia Máxima teórica	750/1020	kW/HP
Frecuencia máxima	1900	rpm
Presión máxima de trabajo	350	bar
Bomba hydráulica	Parker	
Flujo de aceite máximo	1051	L/min
Gasóleo	1820	L
Capacidad DEF (AdBlue)	90	L
El aceite hidráulico	2130	L
Peso sin gasóleo	12430	kg
Peso	14000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT


Specifications

PVE 1000 STAGE V / TIER 4F

Hydraulic Power Pack

USA

Dimensions in inches



Specifications	PVE 1000 STAGE V / TIER 4F	
Diesel Engine	Volvo TAD 1384 VE (2x)	
Max. theoretical power	750/1,020	kW/HP
Max. frequency	1,900	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Parker	
Max. oil flow	278	gal/min
Diesel Fuel	481	gal
DEF (AdBlue) capacity	24	gal
Hydraulic oil	563	gal
Weight without fuel	27,403	lbs
Weight with fuel	30,865	lbs

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Specificatii

PVE 1000 STAGE V / TIER 4F

unitate de putere hidraulica

românesc



Specificatii :	PVE 1000 STAGE V / TIER 4F	
Motor diesel	Volvo TAD 1384 VE (2x)	
Puterea maxima teoretica	750/1020	kW/HP
Frecventa maxima	1900	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Parker	
Debit maxim de ulei	1051	L/min
motorină	1820	L
Capacitate rezervor aditiv AdBlue	90	L
Ulei hidraulic	2130	L
Greutatea fara combustibil	12430	kg
Greutatea cu combustibil	14000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.