

Specification sheet
ICE 3200 STAGE - / TIER 2
Hydraulic Power Pack

English





Specifications :	ICE 3200 STAGE - / TIER 2	
Diesel Engine	Volvo TAD 1643 VE (4x)	
Max. theoretical power	2260/3072	kW/HP
Max. frequency	1850	rpm
Max. operating pressure	350	bar
Hydraulic pump	Rexroth	
Max. oil flow	3330	L/min
Diesel oil	3970	L
DEF (AdBlue) capacity	N.A.	L
Hydraulic oil	4900	L
Weight without fuel	27800	kg
Weight filled up	31000	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Technische Daten

ICE 3200 STAGE - / TIER 2

Aggregat

Deutsch





Technische Daten :	ICE 3200 STAGE - / TIER 2	
Dieselmotor	Volvo TAD 1643 VE (4x)	
Max. theoretische Leistung	2260/3072	kW/HP
Max. Drehzahl	1850	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Rexroth	
Max. Fördermenge	3330	L/min
Diesel Öl	3970	L
DAF (AdBlue) kapazität	N.A.	L
Hydraulische Öl	4900	L
Gewicht ohne Diesel Öl	27800	kg
Gewicht	31000	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Spécifications

ICE 3200 STAGE - / TIER 2

Groupe hydraulique

Français





Spécifications	ICE 3200 STAGE - / TIER 2	
Moteur Diesel	Volvo TAD 1643 VE (4x)	
Puissanse théorique max.	2260/3072	kW/HP
Max. fréquence	1850	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Rexroth	
Débit d'huile max.	3330	L/min
Huile diesel	3970	L
Capacité FED (AdBlue)	N.A.	L
Huile hydraulique	4900	L
Poids sans huile diesel	27800	kg
Poids	31000	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specificaties

ICE 3200 STAGE - / TIER 2

Hydraulisch aggregaat

Nederlands







Specificaties	ICE 3200 STAGE - / TIER 2	
Dieselmotor	Volvo TAD 1643 VE (4x)	
Max. theoretisch vermogen	2260/3072	kW/HP
Max. toerental	1850	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Rexroth	
Max. olie doorstroming	3330	L/min
Diesel olie	3970	L
DEF (AdBlue) capaciteit	N.A.	L
Hydraulische olie	4900	L
Gewicht zonder diesel	27800	kg
Gewicht	31000	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Especificaciones
ICE 3200 STAGE - / TIER 2
Unidat de potencia

Español







Especificaciones	ICE 3200 STAGE - / TIER 2	
Motor de diesel	Volvo TAD 1643 VE (4x)	
Potencia Máxima teórica	2260/3072	kW/HP
Frecuencia máxima	1850	rpm
Presión máxima de trabajo	350	bar
Bomba hydráulica	Rexroth	
Flujo de aceite máximo	3330	L/min
Gasóleo	3970	L
Capacidad DEF (AdBlue)	N.A.	L
El aceite hidráulico	4900	L
Peso sin gasóleo	27800	kg
Peso	31000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specifications


ICE 3200 STAGE - / TIER 2

Hydraulic Power Pack

USA

Dimensions in inches





Specifications	ICE 3200 STAGE - / TIER 2	
Diesel Engine	Volvo TAD 1643 VE (4x)	
Max. theoretical power	2,260/3,072	kW/HP
Max. frequency	1,850	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Rexroth	
Max. oil flow	880	gal/min
Diesel Fuel	1,049	gal
DEF (AdBlue) capacity	N.A.	gal
Hydraulic oil	1,294	gal
Weight without fuel	61,289	lbs
Weight with fuel	68,343	lbs


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specificatii


ICE 3200 STAGE - / TIER 2

unitate de putere hidraulica

românesc







Specificatii :	ICE 3200 STAGE - / TIER 2	
Motor diesel	Volvo TAD 1643 VE (4x)	
Puterea maxima teoretica	2260/3072	kW/HP
Frecventa maxima	1850	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Rexroth	
Debit maxim de ulei	3330	L/min
motorină	3970	L
Capacitate rezervor aditiv AdBlue	N.A.	L
Ulei hidraulic	4900	L
Greutatea fara combustibil	27800	kg
Greutatea cu combustibil	31000	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.