
Specification sheet
ICE 500 STAGE V / TIER 4F
Hydraulic Power Pack

English




Specifications :	ICE 500 STAGE V / TIER 4F	
Diesel Engine	Volvo TAD 1384 VE	
Max. theoretical power	375/510	kW/HP
Max. frequency	1900	rpm
Max. operating pressure	350	bar
Hydraulic pump	Parker	
Max. oil flow	520	L/min
Diesel oil	790	L
DEF (AdBlue) capacity	45	L
Hydraulic oil	1245	L
Weight without fuel	6900	kg
Weight filled up	7600	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Technische Daten
ICE 500 STAGE V / TIER 4F
Aggregat

Deutsch




Technische Daten :	ICE 500 STAGE V / TIER 4F	
Dieselmotor	Volvo TAD 1384 VE	
Max. theoretische Leistung	375/510	kW/HP
Max. Drehzahl	1900	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Parker	
Max. Fördermenge	520	L/min
Diesel Öl	790	L
DAF (AdBlue) kapazität	45	L
Hydraulische Öl	1245	L
Gewicht ohne Diesel Öl	6900	kg
Gewicht	7600	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Spécifications
ICE 500 STAGE V / TIER 4F
Groupe hydraulique

Français



Spécifications	ICE 500 STAGE V / TIER 4F	
Moteur Diesel	Volvo TAD 1384 VE	
Puissanse théorique max.	375/510	kW/HP
Max. fréquence	1900	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Parker	
Débit d'huile max.	520	L/min
Huile diesel	790	L
Capacité FED (AdBlue)	45	L
Huile hydraulique	1245	L
Poids sans huile diesel	6900	kg
Poids	7600	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Specificaties

ICE 500 STAGE V / TIER 4F

Hydraulisch aggregaat

Nederlands




Specificaties	ICE 500 STAGE V / TIER 4F	
Dieselmotor	Volvo TAD 1384 VE	
Max. theoretisch vermogen	375/510	kW/HP
Max. toerental	1900	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Parker	
Max. olie doorstroming	520	L/min
Diesel olie	790	L
DEF (AdBlue) capaciteit	45	L
Hydraulische olie	1245	L
Gewicht zonder diesel	6900	kg
Gewicht	7600	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Especificaciones
ICE 500 STAGE V / TIER 4F
Unidat de potencia

Español



Especificaciones	ICE 500 STAGE V / TIER 4F	
Motor de diesel	Volvo TAD 1384 VE	
Potencia Máxima teórica	375/510	kW/HP
Frecuencia máxima	1900	rpm
Presión máxima de trabajo	350	bar
Bomba hydráulica	Parker	
Flujo de aceite máximo	520	L/min
Gasóleo	790	L
Capacidad DEF (AdBlue)	45	L
El aceite hidráulico	1245	L
Peso sin gasóleo	6900	kg
Peso	7600	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specifications

ICE 500 STAGE V / TIER 4F

Hydraulic Power Pack

USA

Dimensions in inches



Specifications	ICE 500 STAGE V / TIER 4F	
Diesel Engine	Volvo TAD 1384 VE	
Max. theoretical power	375/510	kW/HP
Max. frequency	1,900	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Parker	
Max. oil flow	137	gal/min
Diesel Fuel	209	gal
DEF (AdBlue) capacity	12	gal
Hydraulic oil	329	gal
Weight without fuel	15,212	lbs
Weight with fuel	16,755	lbs


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Specificatii

ICE 500 STAGE V / TIER 4F

unitate de putere hidraulica

românesc



Specificatii :	ICE 500 STAGE V / TIER 4F	
Motor diesel	Volvo TAD 1384 VE	
Puterea maxima teoretica	375/510	kW/HP
Frecventa maxima	1900	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Parker	
Debit maxim de ulei	520	L/min
motorină	790	L
Capacitate rezervor aditiv AdBlue	45	L
Ulei hidraulic	1245	L
Greutatea fara combustibil	6900	kg
Greutatea cu combustibil	7600	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.