
PILING & VIBRO EQUIPMENT


Specification sheet


PVE 1600 STAGE V / TIER 4F

Hydraulic Power Pack

English








Specifications :	PVE 1600 STAGE V / TIER 4F	
Diesel Engine	Caterpillar C18 (2x)	
Max. theoretical power	1126/1510	kW/HP
Max. frequency	1800	rpm
Max. operating pressure	350	bar
Hydraulic pump	Rexroth	
Max. oil flow	1620	L/min
Diesel oil	2150	L
DEF (AdBlue) capacity	N.A.	L
Hydraulic oil	3100	L
Weight without fuel	17870	kg
Weight filled up	19700	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Technische Daten
PVE 1600 STAGE V / TIER 4F
Aggregat

Deutsch








Technische Daten :	PVE 1600 STAGE V / TIER 4F	
Dieselmotor	Caterpillar C18 (2x)	
Max. theoretische Leistung	1126/1510	kW/HP
Max. Drehzahl	1800	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Rexroth	
Max. Fördermenge	1620	L/min
Diesel Öl	2150	L
DAF (AdBlue) kapazität	N.A.	L
Hydraulische Öl	3100	L
Gewicht ohne Diesel Öl	17870	kg
Gewicht	19700	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Spécifications
PVE 1600 STAGE V / TIER 4F
Groupe hydraulique

Français







Spécifications	PVE 1600 STAGE V / TIER 4F	
Moteur Diesel	Caterpillar C18 (2x)	
Puissanse théorique max.	1126/1510	kW/HP
Max. fréquence	1800	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Rexroth	
Débit d'huile max.	1620	L/min
Huile diesel	2150	L
Capacité FED (AdBlue)	N.A.	L
Huile hydraulique	3100	L
Poids sans huile diesel	17870	kg
Poids	19700	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT


Specificaties


PVE 1600 STAGE V / TIER 4F

Hydraulisch aggregaat

Nederlands








Specificaties	PVE 1600 STAGE V / TIER 4F	
Dieselmotor	Caterpillar C18 (2x)	
Max. theoretisch vermogen	1126/1510	kW/HP
Max. toerental	1800	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Rexroth	
Max. olie doorstroming	1620	L/min
Diesel olie	2150	L
DEF (AdBlue) capaciteit	N.A.	L
Hydraulische olie	3100	L
Gewicht zonder diesel	17870	kg
Gewicht	19700	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Especificaciones
PVE 1600 STAGE V / TIER 4F
Unidat de potencia

Español







Especificaciones	PVE 1600 STAGE V / TIER 4F	
Motor de diesel	Caterpillar C18 (2x)	
Potencia Máxima teórica	1126/1510	kW/HP
Frecuencia máxima	1800	rpm
Presión máxima de trabajo	350	bar
Bomba hydráulica	Rexroth	
Flujo de aceite máximo	1620	L/min
Gasóleo	2150	L
Capacidad DEF (AdBlue)	N.A.	L
El aceite hidráulico	3100	L
Peso sin gasóleo	17870	kg
Peso	19700	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT


Specifications


PVE 1600 STAGE V / TIER 4F


Hydraulic Power Pack

USA

Dimensions in inches







Specifications	PVE 1600 STAGE V / TIER 4F	
Diesel Engine	Caterpillar C18 (2x)	
Max. theoretical power	1,126/1,510	kW/HP
Max. frequency	1,800	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Rexroth	
Max. oil flow	428	gal/min
Diesel Fuel	568	gal
DEF (AdBlue) capacity	N.A.	gal
Hydraulic oil	819	gal
Weight without fuel	39,397	lbs
Weight with fuel	43,431	lbs

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT


Specificatii


PVE 1600 STAGE V / TIER 4F

unitate de putere hidraulica

românesc







Specificatii :	PVE 1600 STAGE V / TIER 4F	
Motor diesel	Caterpillar C18 (2x)	
Puterea maxima teoretica	1126/1510	kW/HP
Frecventa maxima	1800	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Rexroth	
Debit maxim de ulei	1620	L/min
motorină	2150	L
Capacitate rezervor aditiv AdBlue	N.A.	L
Ulei hidraulic	3100	L
Greutatea fara combustibil	17870	kg
Greutatea cu combustibil	19700	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.