
PILING & VIBRO EQUIPMENT


Specification sheet


PVE 1600 STAGE V / TIER 4F

Hydraulic Power Pack

English








Specifications :	PVE 1600 STAGE V / TIER 4F	
Diesel Engine	Volvo Penta TWD 1683 VE (2x)	
Max. theoretical power	1170/1592	kW/HP
Max. frequency	1900	rpm
Max. operating pressure	350	bar
Hydraulic pump	Rexroth	
Max. oil flow	1710	L/min
Diesel oil	2150	L
DEF (AdBlue) capacity	140	L
Hydraulic oil	3100	L
Weight without fuel	17870	kg
Weight filled up	19700	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Technische Daten
PVE 1600 STAGE V / TIER 4F
Aggregat

Deutsch








Technische Daten :	PVE 1600 STAGE V / TIER 4F	
Dieselmotor	Volvo Penta TWD 1683 VE (2x)	
Max. theoretische Leistung	1170/1592	kW/HP
Max. Drehzahl	1900	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Rexroth	
Max. Fördermenge	1710	L/min
Diesel Öl	2150	L
DAF (AdBlue) kapazität	140	L
Hydraulische Öl	3100	L
Gewicht ohne Diesel Öl	17870	kg
Gewicht	19700	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Spécifications
PVE 1600 STAGE V / TIER 4F
Groupe hydraulique

Français







Spécifications	PVE 1600 STAGE V / TIER 4F	
Moteur Diesel	Volvo Penta TWD 1683 VE (2x)	
Puissanse théorique max.	1170/1592	kW/HP
Max. fréquence	1900	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Rexroth	
Débit d'huile max.	1710	L/min
Huile diesel	2150	L
Capacité FED (AdBlue)	140	L
Huile hydraulique	3100	L
Poids sans huile diesel	17870	kg
Poids	19700	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT


Specificaties


PVE 1600 STAGE V / TIER 4F

Hydraulisch aggregaat

Nederlands








Specificaties	PVE 1600 STAGE V / TIER 4F	
Dieselmotor	Volvo Penta TWD 1683 VE (2x)	
Max. theoretisch vermogen	1170/1592	kW/HP
Max. toerental	1900	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Rexroth	
Max. olie doorstroming	1710	L/min
Diesel olie	2150	L
DEF (AdBlue) capaciteit	140	L
Hydraulische olie	3100	L
Gewicht zonder diesel	17870	kg
Gewicht	19700	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT

Especificaciones
PVE 1600 STAGE V / TIER 4F
Unidat de potencia

Español







Especificaciones	PVE 1600 STAGE V / TIER 4F	
Motor de diesel	Volvo Penta TWD 1683 VE (2x)	
Potencia Máxima teórica	1170/1592	kW/HP
Frecuencia máxima	1900	rpm
Presión máxima de trabajo	350	bar
Bomba hydráulica	Rexroth	
Flujo de aceite máximo	1710	L/min
Gasóleo	2150	L
Capacidad DEF (AdBlue)	140	L
El aceite hidráulico	3100	L
Peso sin gasóleo	17870	kg
Peso	19700	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

PILING & VIBRO EQUIPMENT


Specifications

PVE 1600 STAGE V / TIER 4F

Hydraulic Power Pack

USA

Dimensions in inches



Specifications	PVE 1600 STAGE V / TIER 4F	
Diesel Engine	Volvo Penta TWD 1683 VE (2x)	
Max. theoretical power	1,170/1,592	kW/HP
Max. frequency	1,900	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Rexroth	
Max. oil flow	452	gal/min
Diesel Fuel	568	gal
DEF (AdBlue) capacity	37	gal
Hydraulic oil	819	gal
Weight without fuel	39,397	lbs
Weight with fuel	43,431	lbs

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


PILING & VIBRO EQUIPMENT


Specificatii


PVE 1600 STAGE V / TIER 4F

unitate de putere hidraulica

românesc







Specificatii :	PVE 1600 STAGE V / TIER 4F	
Motor diesel	Volvo Penta TWD 1683 VE (2x)	
Puterea maxima teoretica	1170/1592	kW/HP
Frecventa maxima	1900	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Rexroth	
Debit maxim de ulei	1710	L/min
motorină	2150	L
Capacitate rezervor aditiv AdBlue	140	L
Ulei hidraulic	3100	L
Greutatea fara combustibil	17870	kg
Greutatea cu combustibil	19700	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.