


Specification sheet
ICE 3200 STAGE V / TIER 4F
Hydraulic Power Pack

English









Specifications :	ICE 3200 STAGE V / TIER 4F	
Diesel Engine	Volvo TWD 1683 VE (4x)	
Max. theoretical power	2340/3184	kW/HP
Max. frequency	1900	rpm
Max. operating pressure	350	bar
Hydraulic pump	Rexroth	
Max. oil flow	3420	L/min
Diesel oil	3800	L
DEF (AdBlue) capacity	280	L
Hydraulic oil	6300	L
Weight without fuel	32300	kg
Weight filled up	35500	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Technische Daten
ICE 3200 STAGE V / TIER 4F
Aggregat

Deutsch









Technische Daten :	ICE 3200 STAGE V / TIER 4F	
Dieselmotor	Volvo TWD 1683 VE (4x)	
Max. theoretische Leistung	2340/3184	kW/HP
Max. Drehzahl	1900	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Rexroth	
Max. Fördermenge	3420	L/min
Diesel Öl	3800	L
DAF (AdBlue) kapazität	280	L
Hydraulische Öl	6300	L
Gewicht ohne Diesel Öl	32300	kg
Gewicht	35500	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Spécifications
ICE 3200 STAGE V / TIER 4F
Groupe hydraulique

Français







Spécifications	ICE 3200 STAGE V / TIER 4F	
Moteur Diesel	Volvo TWD 1683 VE (4x)	
Puissanse théorique max.	2340/3184	kW/HP
Max. fréquence	1900	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Rexroth	
Débit d'huile max.	3420	L/min
Huile diesel	3800	L
Capacité FED (AdBlue)	280	L
Huile hydraulique	6300	L
Poids sans huile diesel	32300	kg
Poids	35500	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specificaties


ICE 3200 STAGE V / TIER 4F

Hydraulisch aggregaat

Nederlands









Specificaties	ICE 3200 STAGE V / TIER 4F	
Dieselmotor	Volvo TWD 1683 VE (4x)	
Max. theoretisch vermogen	2340/3184	kW/HP
Max. toerental	1900	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Rexroth	
Max. olie doorstroming	3420	L/min
Diesel olie	3800	L
DEF (AdBlue) capaciteit	280	L
Hydraulische olie	6300	L
Gewicht zonder diesel	32300	kg
Gewicht	35500	kg


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.

Especificaciones
ICE 3200 STAGE V / TIER 4F
Unidat de potencia

Español







Especificaciones	ICE 3200 STAGE V / TIER 4F	
Motor de diesel	Volvo TWD 1683 VE (4x)	
Potencia Máxima teórica	2340/3184	kW/HP
Frecuencia máxima	1900	rpm
Presión máxima de trabajo	350	bar
Bomba hydráulica	Rexroth	
Flujo de aceite máximo	3420	L/min
Gasóleo	3800	L
Capacidad DEF (AdBlue)	280	L
El aceite hidráulico	6300	L
Peso sin gasóleo	32300	kg
Peso	35500	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specifications


ICE 3200 STAGE V / TIER 4F


Hydraulic Power Pack

USA

Dimensions in inches







Specifications	ICE 3200 STAGE V / TIER 4F	
Diesel Engine	Volvo TWD 1683 VE (4x)	
Max. theoretical power	2,340/3,184	kW/HP
Max. frequency	1900,	rpm
Max. operating pressure	5076,3	psi
Hydraulic pump	Rexroth	
Max. oil flow	903	gal/min
Diesel Fuel	1003,9	gal
DEF (AdBlue) capacity	74	gal
Hydraulic oil	1664,3	gal
Weight without fuel	71209,3	lbs
Weight with fuel	78264,1	lbs


Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.


Specificatii


ICE 3200 STAGE V / TIER 4F

unitate de putere hidraulica

românesc







Specificatii :	ICE 3200 STAGE V / TIER 4F	
Motor diesel	Volvo TWD 1683 VE (4x)	
Puterea maxima teoretica	2340/3184	kW/HP
Frecventa maxima	1900	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Rexroth	
Debit maxim de ulei	3420	L/min
motorină	3800	L
Capacitate rezervor aditiv AdBlue	280	L
Ulei hidraulic	6300	L
Greutatea fara combustibil	32300	kg
Greutatea cu combustibil	35500	kg

Dieseko group B.V. All rights reserved. No part of this publication may be reproduced and/or published in any manner whatsoever without prior written permission from Dieseko group B.V.